

HEATIT Z-WAVE

An innovative thermostat incorporating Z-Wave technology for regulating electric floor heating.



#heatit

5430498

HEATIT Z-WAVE

White RAL 9003 Color and design matching



Black RAI 9011




Design matching the Schneider Exxact series.

Heatit Z-Wave is an electronic thermostat for flush mounting in a standard wall box. The thermostat has a built-in Z-Wave chip that can be connected with Home Automation systems like Fibaro, POPP, Vera, Zipato etc.

WAVE

The thermostat is equipped with sensitive cap sense buttons. By lightly pressing the buttons, the display will show the set value.

Heatit Z-Wave is equipped with a single-pole switch. The thermostat can handle loads up to 16A/3600W at 230V. If the load is greater than this, the thermostat needs to be connected to a contactor. It can be used with two external temperature sensors. The thermostat has the capacity of up to 8 associations (relays, wall plugs etc.)



PRODUCT INFO Heatit 7-Wave SW 18

FEATURES

Floor sensor

External room sensor

Temperature limiter

Power regulator

Z-Wave Plus chip, 500 series

Weekly program

Setback mode via gateway or pilot wire

7-segment LCD-screen

Can be used in connection with different NTC-sensor

Lock mode/child lock

Backlight

Calibration

8 associations

TECHNICAL DATA

Protocol: Z-Wave, EU 868,42 MHz

- other frequencies on request

Rated voltage: 230V 50/60Hz

Max load: 3600W (resistive load)

750W self-limiting heating cable

Max current: 16A Power consumption: 1.5W

Power regulator: Time cycle 0-30min

-20°C to 40°C Min/max installation temp: Min/max operating temp: 5°C to 40°C

Floor sensor 5°C to 40°C Temperature intervals:

External room sensor 5°C to 40°C

0,3°C to 3,0°C (default 0,5°C) Hysteresis:

Sensor values: 0°C 29,1 kOhm

18.6 kOhm 10°C 15.1 kOhm 15°C 20°C 12,2 kOhm 25°C 10,0 kOhm

Switch: Single-pole switch

IP class: IP21

Use 1,5mm² or 2,5mm² according to load.

INCLUDED IN PACKAGE

Floor sensor 3 meters, Art. no. 5430109

WARRANTY

2 years

The thermostat is designed for electrical heating.





SENSORS



5430108

FLOOR SENSOR Ø3MM

NTC 10 kOhm @ 25°C Cable length 6 meters



5430128

EXTERNAL ROOM SENSOR

External room sensor with glass front face. Wall mounted. NTC 10 kOhm

Size: (LxWxH) 80x110mmx16mm



5430109

FLOOR SENSOR Ø4MM

Standard sensor for Heatit NTC 10 kOhm @ 25°C Cable length 3 meters



5430129

EXTERNAL ROOM SENSOR, MINI

NTC 10 kOhm @ 25°C Size: (LxWxH) 40x60x47mm Max. length of power supply

cable: 50 meters

ART. NO.	PRODUCT	COLOR	EAN-NO.	EU FREQUENCY	RU FREQUENCY
5430499	Heatit Z-Wave thermostat 3600W 16A	White RAL 9003	7071236011934	EU 868,42 MHz	RU 869,0 MHz
5430498	Heatit Z-Wave thermostat 3600W 16A	Black RAL 9011	7071236011927	EU 868,42 MHz	RU 869,0 MHz
5430311	Frame for Heatit	White RAL 9003	7071236011866		
5430312	Frame for Heatit	Black RAL 9011	7071236011873		
5430497	Cable for software update on thermostat				
5430108	Floor sensor Ø3mm 6m NTC 10 kOhm		7071236007739		
5430109	Floor sensor Ø4mm 3m NTC 10 kOhm		7071236005353		
5430128	External room sensor NTC 10 kOhm				
5430129	External room sensor, mini, NTC 10 kOhm		7071236008293		

